

High Gloss Sealer

Advanced Water-Based Acrylic Emulsion Sealer

- Dries to a Clear Glossy Finish
- 100% Acrylic Formula
- Fast Drying
- Durable Lasting Finish



Revised: 03/13

Manufacturer:

FarmPaint.com
700 Phillips Lane
Lexington, KY 40504
877-441-3276

Description

A 100% Water-Based Acrylic Clear Sealer that provides a high gloss protective and durable finish to paving stone and exposed aggregate surfaces.

Uses

- Paving Stone, Decorative Stone, and Exposed Aggregate Concrete

Surface Preparation

- Clean Surface - Sweep all dirt and loose debris from surface. Remove all oil, grease and foreign materials. Surface must be completely dry before applying High Gloss Sealer.

Application

Stir pail thoroughly. Apply thin even coats of sealer with a roller. Additional coats may be applied to achieve desired level of gloss and finish. Allow material to dry thoroughly between coats.

Drying Time

Allow 24 hours to dry, depending on weather conditions.

Clean Up

Wash tools with water before material dries.

Weather Conditions

- Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24 hour period.
- In areas where dew or fog accumulates in the

early evening, it is best to coat in the morning.

Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.

- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

- 130 to 170 square feet per gallon per coat. A 4.75 gallon pail will cover approximately 600-800 square feet.

Precautions

- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 150 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying
- Warning: This Product Contains Chemicals Known To The State Of California To Cause Cancer And Birth Defects Or Other Reproductive Harm

High Gloss Sealer
Advanced Water-Based Acrylic Emulsion Sealer

Form No.: FP-TD14705

Packaging

Item #	Container Size	Pack	Weight
14705	4.75 Gallon Pail	1	46 lbs.
14701	.9 Gallon Pail	6	55 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Water	7732-18-5
Acrylic Emulsion Polymer	Proprietary