

# Concrete Patch

100% Acrylic Formula for Tough, Durable Repairs

- 100% Acrylic Formulation
- Fills Cracks Up To 1" Wide
- Heavy-Bodied Trowel Grade Formula
- Repairs Damaged & Spalled Areas Up to 1/4" Deep
- Dries Neutral/Sand



Revised: 11/10

### Manufacturer:

FarmPaint.com  
700 Phillips Lane  
Lexington, KY 40504  
877-441-3276

### Description

A 100% acrylic heavy-bodied trowel grade crack filler designed for filling larger cracks up to 1" wide in concrete surfaces. Concrete Patch can also be used to fill and repair damaged and spalled areas in concrete up to 1/4" deep.

### Uses

- Use to Repair Concrete Driveways, Floors, Patios, Sidewalks, Pool Decks, & More

### Surface Preparation

- **Cleaning Cracks** - Remove dirt and vegetation from cracks with screwdriver or other suitable instrument. Flush out crack with water and allow to dry.
- **Damaged and Spalled Areas** - Remove dirt and debris from repair area. Scrub thoroughly with wire brush and rinse with water.

### Application

Apply material with rectangular trowel or wide putty knife. Spread and smooth out material flush to adjoining surface.

### Drying Time

Allow material to dry and cure for 48 hours prior to resuming foot or vehicle traffic.

### Clean Up

Wash tools with water before material dries.

### Weather Conditions

- Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24 hour period.
- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

### Coverage (Approximate)

- Coverage will vary, depending on width and depth of repair.

### Precautions

- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

### Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 150 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying
- Warning: This Product Contains Chemicals Known To The State Of California To Cause Cancer And Birth Defects Or Other Reproductive Harm

**Concrete Patch**  
100% Acrylic Formula for Tough, Durable Repairs

Form No.: FP-TD14711

## Packaging

| Item # | Container Size | Pack | Weight    |
|--------|----------------|------|-----------|
| 14711  | .9 Gallon Pail | 6    | 99.8 lbs. |

\* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

| Ingredients:    | Cas No.     |
|-----------------|-------------|
| Water           | 7732-18-5   |
| Acrylic Polymer | Proprietary |
| Fiber           | 9004-34-6   |
| Ester Alcohol   | 25265-77-4  |
| Silicon Dioxide | 14808-60-7  |