

Concrete Crack Sealant

100% Acrylic Elastomeric Sealant

- Seals Out Moisture
- Fills Cracks Up To 1/2" Wide
- High Solids Formulation for Lasting Repair
- 100% Acrylic Elastomeric Formula
- Dries Neutral/Sand



Revised: 03/13

Manufacturer:

FarmPaint.com
700 Phillips Lane
Lexington, KY 40504
877-441-3276

Description

A 100% acrylic elastomeric sealant designed for filling cracks up to 1/2" wide in concrete pavement surfaces.

Uses

Filling Cracks in Concrete Pavement Surfaces

Surface Preparation

- **Cleaning Cracks** - Remove dirt and vegetation from cracks with screwdriver or other suitable instrument. Flush out crack with water and allow to dry.

Application

Mix contents of container by moderately shaking. Cut top of spout to desired width (smaller than width of crack). Fill cracks and smooth flush to adjoining pavement with putty knife. Allow crack sealant to dry for 24 hours. If desired, a second application may be applied.

Drying Time

Allow Crack Sealant to cure 24 hours before resuming traffic.

Clean Up

Wash tools with water before material dries.

Weather Conditions

- Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24 hour period.

- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

- Coverage is dependent upon depth and width of cracks. Typically, one quart of Concrete Crack Sealant will fill approximately 20-35 feet of cracks.

Precautions

- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 100 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying
- Warning: This Product Contains Chemicals Known To The State Of California To Cause Cancer And Birth Defects Or Other Reproductive Harm

Concrete Crack Sealant
100% Acrylic Elastomeric Sealant

Form No.: FP-TD14724

Packaging

Item #	Container Size	Pack	Weight
14724	.9 Quart Bottle	12	39 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Water	7732-18-5
Acrylic Polymer	Proprietary
Calcium Carbonate	16389-88-1