

5-Year Driveway Filler & Sealer

Polymer Modified Asphalt Emulsion Based Driveway Filler & Sealer

- 5-Year Protection
- 5X Polymer Modification
- Fills & Seals Blacktop Surfaces
- Dries Black



Revised: 11/10

Manufacturer:

FarmPaint.com
700 Phillips Lane
Lexington, KY 40504
877-441-3276

Description

A polymer modified asphalt emulsion based driveway filler and sealer designed to beautify and protect asphalt pavement surfaces. Fortified with sand for added filling, slip resistance, and durability.

Uses

- Asphalt driveways & parking areas
- All asphalt pavement must weather at least six (6) months, including one summer, before using this product.
- DO NOT use on concrete surfaces.

Surface Preparation

- All cracks and holes should be repaired with FarmPaint.com Elastomeric Pourable Driveway Crack Filler or FarmPaint.com Trowel Grade Crack Filler. Allow repaired areas to cure as directed before sealing.
- For best results, surface must be thoroughly cleaned. Remove all loose dirt and foreign material and scrub all grease and oil spots with a detergent to prevent subsequent peeling and flaking. Flush entire pavement clean with water, being sure to not leave standing water.

Application

Stir sealer to a uniform consistency and continue to stir throughout application. With pavement still damp, apply a uniform coat of sealer, being sure to avoid heavy or uneven application which may result in cracking or tracking. A second coat should be applied after the first coat has dried "to the

touch" or within 24 hours at stated coverage rate. A rubber squeegee or brush is recommended for application.

Drying Time

Allow FarmPaint.com Driveway Filler & Sealer to dry to the touch, approximately 3 to 6 hours, depending on weather conditions. Allow product to cure at least 8 to 24 hours under ideal conditions (70 °F and less than 50% humidity), testing for trafficability before opening area to regular use.

Clean Up

Wash tools with water before material dries.

Weather Conditions

- Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24 hour period.
- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

- Depending on pavement porosity, coverage will vary from 250-350 sq. ft. per 4.75 gallon pail.

Precautions

- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

5-Year Driveway Filler & Sealer
Polymer Modified Asphalt Emulsion Based Driveway Filler & Sealer

Form No.: FP-TD15555

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 50 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying
- Warning: This Product Contains Chemicals Known To The State Of California To Cause Cancer And Birth Defects Or Other Reproductive Harm

Packaging

Item #	Container Size	Pack	Weight
15557	55 Gallon Drum	1	625 lbs.
15555	4.75 Gallon Pail	1	58 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Hydrous Aluminum Silicate	1332-58-7
Silicon Dioxide	14808-60-7
Water	7732-18-5
Blend of Fatty Amines	Proprietary
Polymer	Proprietary