Elastomeric Pourable Driveway Crack Filler

Polymer Modified Asphalt Emulsion Based Crack Sealant

- Elastomeric Formula for Outstanding Flexibility & Adhesion
- Fills & Seals Cracks in Asphalt Driveways
- Seals Out Moisture
- High Solids Formula for Lasting Repair
- Dries Black

Manufacturer:
FarmPaint.com
700 Phillips Lane
Lexington, KY 40504
877-441-3276

Description
A polymer modified elastomeric asphalt emulsion crack sealant designed for sealing cracks up to 3/4" wide in asphalt pavement surfaces.

Uses
- All types of asphalt pavements.
- DO NOT USE on concrete or masonry surfaces.
- Do not apply to cracks/holes containing water.

Surface Preparation
Proper preparation of the crack to be treated is vital to ensuring maximum performance. Use a stiff brush to remove all loose material, dirt, oil, vegetation and existing sealants. Cracks deeper than 1" should be filled with backer-rod or a suitable material to 1/2" depth.

Application
Shake well before using. Using pour spout, pour product into crack slightly above surface level. Material may settle, requiring a second application. Always allow 24 hours between applications.

Drying Time
Depending on weather conditions, Crack Sealant will develop a skinned surface that may be opened to traffic in 1 to 12 hours. However, to assure a traffic-resistant surface, the pavement should be closed to traffic for 12 to 24 hours from application. Always test for trafficability before opening for regular use.

Clean Up
Wash tools with water before material dries.

Weather Conditions
- Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 40 °F within a 24 hour period.
- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)
- For estimation purposes, up to 150 lineal feet per gallon for cracks 1/2" x 1/4" deep.

Precautions
- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 ºF

Safety And Environmental Precautions
- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 10 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Revised: 11/10

Elastomeric Pourable Driveway Crack Filler
Polymer Modified Asphalt Emulsion Based Crack Sealant

Form No.: FP-TD15571

- Warning: This Product Contains Chemicals Known To The State Of California To Cause Cancer And Birth Defects Or Other Reproductive Harm

Packaging

Item #	Container Size	Pack	Weight
65571	.9 Gallon	6	62.3 lbs.

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Quartz	14808-60-7
Synthetic Rubber	108-18-5
Water	7732-18-5
Alum. Silicate	1332-58-7

Copyright © 2010, FarmPaint.com
All rights reserved.

700 Phillips Lane • Lexington, KY 40504
Phone: 877-441-3276

Form No.: FP-TD15571
Revised: 11/10