

7-Year Premium Fibered Aluminum Roof Coating

Formulated With High Grade Aluminum Pigments

- 7 -Year Protection
- Stays Brighter Longer
- Bright Silver Color
- Premium Energy Saving Formula
- Meets ASTM D 1227, Type III
- Dries Bright Silver



Revised: 10/15

Manufacturer:

FarmPaint.com
700 Phillips Lane
Lexington, KY 40504
877-441-3276

Description

This premium energy saving formula seals, protects and reflects solar heat using selected waterproofing asphalts, fibers and high grade leafing aluminum pigments. Forms an excellent adhesive bond with most substrates. Areas immediately under roof will remain approximately 15-20 degrees cooler in summer. In winter, inside heat is reflected back into the building, saving energy costs.

Uses

- Agricultural Buildings, Silos & Grain Bins
- Metal & Built-up Roofs
- Weathered Asphalt Coatings
- Mobile Homes/RV's
- Mod. Bitumen, SBS/APP

Surface Preparation

Repair all cracks, splits, and holes using FarmPaint.com All Weather Roof Cement and Reinforcing Fabric, adhering to the directions on their label. Allow repairs to weather at least 30 days before coating. Clean surfaces thoroughly by brooming away dirt, dust and loose particulate. Remove all grease and oil using detergent and water, rinsing thoroughly. Broom away excess water and allow to dry completely.

Application

Mix coating thoroughly before and during application. Uniformly coat the entire surface with the coating using a roofing brush or roller. Do not apply to roofs which hold water. Standing water will result in premature failure.

Drying Time

Allow 24 hours to dry, depending on weather conditions.

Clean Up

Clean tools with mineral spirits in well ventilated area immediately after use.

Weather Conditions

- Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24 hour period.
- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

- Metal Roofs: 75-100 sq. ft. per gallon
- Composition Roofs: 50-75 sq. ft. per gallon

Precautions

- Combustible. Contains Petroleum Distillate.
- Do Not Heat Or Thin
- Keep Away From Heat And Flame
- Do Not Store At Temperatures Above 100 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container

7-Year Premium Fibered Aluminum Roof Coating
Formulated With High Grade Aluminum Pigments

Form No.: FP-TD19465

- Volatile Organic Content (VOC) Is 370 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying
- Warning: This Product Contains Chemicals Known To The State Of California To Cause Cancer And Birth Defects Or Other Reproductive Harm

Packaging

| Item # | Container Size | Pack | Weight |
|--------|------------------|------|---------|
| 19465 | 4.75 Gallon Pail | 1 | 40 lbs. |
| 19461 | .9 Gallon Pail | 6 | 58 lbs. |

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

| Ingredients: | Cas No. |
|-------------------|------------|
| Asphalt | 8052-42-4 |
| Stoddard Solvent | 64742-88-7 |
| Aluminum Flake | 7429-90-5 |
| Cellulose | 9004-34-6 |
| Calcium Carbonate | 1317-65-3 |