

Fibered Roof & Foundation Coating

Water Resistant Asphalt Based Coating

- Seals, Protects & Waterproofs
- Use Above or Below Grade
- Meets ASTM D 4479
- Dries Black



Revised: 11/10

Manufacturer:

FarmPaint.com
700 Phillips Lane
Lexington, KY 40504
877-441-3276

Description

A mixture of liquid asphalt and fibers designed to form a tough, adhesive bond with most roof surfaces. This material will seal small cracks, joints, seams and nail holes. Highly resistant to water and other types of weather damage.

Uses

- Metal Roofs
- Concrete Roofs
- Built-Up Roofs
- Concrete Foundations
- Roof Felts, Wood Roofs & More

Surface Preparation

Clean surface with brush or broom, removing all loose sediment and dirt. Nail down any loose parts. Repair any leaking or weak areas with FarmPaint.com All Weather Roof Cement and Reinforcing Fabric repair material.

Application

Coat entire surface area with Fibered Roof and Foundation Coating. For best results, apply a uniform coating with roofing brush when surface is dry. One coat provides year round protection.

Drying Time

Allow 24 hours to dry, depending on weather conditions.

Clean Up

Clean tools with mineral spirits in well ventilated area immediately after use.

Weather Conditions

- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

- Metal Roofing: 60-70 sq. ft. per gallon
- Felt or Composition: 50-60 sq. ft. per gallon
- Concrete or Masonry Surfaces: 25-50 sq. ft. per gallon
- Strip Composition or Dried Out Roofing: 25-50 sq. ft. per gallon

Precautions

- Combustible. Contains Petroleum Distillate.
- Do Not Heat Or Thin
- Keep Away From Heat And Flame
- Do Not Store At Temperatures Above 100 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 250 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying
- Warning: This Product Contains Chemicals Known To The State Of California To Cause Cancer And Birth Defects Or Other Reproductive Harm

Fibered Roof & Foundation Coating
Water Resistant Asphalt Based Coating

Form No.: FP-TD19515

Packaging

| Item # | Container Size | Pack | Weight |
|--------|------------------|------|---------|
| 19515 | 4.75 Gallon Pail | 1 | 44 lbs. |
| 19511 | .9 Gallon Pail | 6 | 52 lbs. |

* At time of manufacturing, containers are filled to maximum. However, due to the reduction in volume that occurs after cooling and settling, the actual volume may be less.

| Ingredients: | Cas No. |
|---------------------|------------|
| Petroleum Asphalt | 8052-42-4 |
| Mineral Spirits | 64742-88-7 |
| Calcium Carbonate | 1317-65-3 |
| Cellulose Fibers | 9004-34-6 |
| Magnesium Carbonate | 546-93-0 |