



## Primer Coat

Revised: 03/13

### DESCRIPTION

A superior rubberized primer that is ideal for use with LIQUID FENCE FINISH COAT. Forms a tenacious bond to both old and new surfaces. Remains flexible down to -20 °F. Easily applied by spray, brush or roller.

### Directions

Surface shall be clean, dry and free of any dirt or contaminants. Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24-hour period. Be sure to wear eye protection and gloves when mixing and applying this product. In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application. Stir container thoroughly. Apply by brush, roller, or airless spray (suggested tip size .021 to .025). Clean tools with water immediately after use.

### Features

- Remains Flexible Down to -20° F
- Creates Superior Adhesion to Both Old & New Wood or Metal Surfaces
- Ideal for Fences & Buildings (Wood or Metal)
- Ideal for Use with LIQUID FENCE FINISH COAT
- Nature-Friendly Solvent-Free Water Based Technology
- Equine & Livestock Friendly
- Non-Toxic

### COVERAGE

4-Board Wood Plank Fence: 1.75 to 2 panels per gallon  
 Larger Areas: 100-125 square feet per gallon

### DRYING TIME

Dry to the touch in 2-3 hours.

### CAUTION

Avoid breathing vapors and contact with eyes and

skin. Do not take internally. Clean hands thoroughly after using. KEEP OUT OF REACH OF CHILDREN.

### FIRST AID

If swallowed, CALL A PHYSICIAN IMMEDIATELY. In case of eye contact, open eyelids widely and flush with large quantities of fresh, potable water for at least 15 minutes. GET MEDICAL ATTENTION. For skin contact, wash thoroughly with waterless hand cleaner. Remove and launder contaminated clothing before reuse. In case of inhalation, move to fresh air. Apply artificial respiration if breathing stops. Give Oxygen. If product is ingested, do not induce vomiting. OBTAIN MEDICAL ATTENTION IMMEDIATELY. SEEK MEDICAL ATTENTION IF SYMPTOMS PERSIST.

PROTECT CONTAINER FROM FREEZING.

### ATTENTION

Empty containers may retain material residues. Dispose of empty container in accordance with local, state, and federal regulations based upon chemical composition of contents.

### VOC

Less than 100 gm/Liter Max

### LIMITED WARRANTY

The statements made on this container are believed to be true and accurate and are intended to provide a guide for approved application practices. As workmanship, weather, construction, condition of pavement, tools utilized, and other variables affecting results are all beyond our control, the manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. The manufacturer expressly disclaims any implied warranties of merchantability or fitness for a particular purpose. Warranty is void on multi-coat applications if material made by other manufacturers is used with this product.

**MADE IN USA**

Liquid Fence  
Primer Coat

Form No.: EC-LFPC001

**PACKAGING**

Liquid Fence is packaged in 5 gallon pails, 55 gallon drums, & 275 gallon totes.